

MPK10.2

2IN1 MINIPICKER:
GLASS ROBOT & PICK&CARRY CRANE



Lifting capacity

2,180 lb



Max tip height

17' 1"



Dimensions (l x w x h)

7'6" x 3'2" x 4'11"



Powered by

Battery



Weight

2,810 lb

2,304 lb machine
507 lb removable ballast



EN [ft - lb]




WORKING MODES




VACUUM MANIPULATOR 2,180 lb

- Up to 10 pads, modular layout
- Electrically operated via wired control or radio control
- Vacuum pump on-board
- Two independent vacuum circuits
- 360° rotation, tilt and swing
- Ø1'4" or Ø11" pads for glass, marble and slabs
- Special pads for monopanel
- "Blow-off" function for easy release
- Ball joint on pads for improved adaptability


ENDLESS PADS CONFIGURATIONS




Standard




10 pads - Ø1'4" & Ø11"



Ø1'4" in-line




Ø11" in-line





Monopanel

and more...

Manipulator Load Chart



+47/-96 Tilt



SEARCHER HOOK

2,180 lb

- 4 angles: +15° / 0° / -30° / -60°
- Increases versatility
- Stowed onboard





MANIPULATOR HOOK

1,320 lb

- Quickly installed on manipulator frame
- Electrical tilt and swing

HOOK

2,180 lb





RADIO REMOTE CONTROL * BOOM MOBILITY

- Controls machine driving, crane and manipulator
- Simple and intuitive, proportional
- Spare battery on board
- Wired control also available
- Self-diagnostics & emergency button

- Turret side rotation $\pm 9^\circ$
- -21° to $+58^\circ$ boom angle
- Double hydraulic boom extensions

FULLY ELECTRIC

- Battery powered, Lead-acid type 24 V 310 Ah
- Minimal maintenance costs
- Emission-free indoor operation
- On board 110V or 230V fast battery charger
- Runtime over 1 workday



MODULAR BALLAST

- Easily removable ballast modules
- Operates with reduced ballast
- Automatic lifting capacity adjustment
- 507 lb total weight



EASY TO DRIVE EVERYWHERE

- Front-wheel drive with differential
- Wide steering angle
- Side stabilisers
- Twin front wheels available *



OUTDOOR-INDOOR WHEELS

- Off-road tyres (foamed puncture-proof)
- Non-marking white tyres for indoor *



J-LINK POWERED BY TRACKUNIT*

- Remote fleet monitoring and diagnostics
- Built-in or retrofit on existing units



*Optional



MPK10.2
2IN1 MINIPICKER

Jekko USA • info@jekkousa.com • www.jekkousa.com • (800) 670-4103

Specifications are subject to change without notice.

All data provided is for reference purposes only and is not legally binding.

V25.06